

INOX (A.Q.S.)



Boiler Electric

80 la 500 Litrii

Principais Caraterísticas

Cuva din oțel inoxidabil AISI 316L;  
Nu are nevoie de un anod de magneziu;  
Densitate mare de izolare din poliuretan.

Descrição do Produto

Incalzitoare de stocare a apei construite din otel inoxidabil AISI 316L, extrem de rezistent la coroziune de perforații, toate sudurile efectuate de TIG eliminându-se astfel orice posibilitate de coroziune interstițială. Disponibil cu capacități de la 80 la 500 de litri.

Modelos e Preços

Código	Modelo
0204-0201	Electrical Water Heater 80l (wall mounted)
0204-0202	Electrical Water Heater 100l (with feet)
0204-0203	Electrical Water Heater 150l (wall mounted)
0204-0103 *	Electrical Water Heater 150l (with feet)
0204-0204	Electrical Water Heater 200l (wall mounted)
0204-0104 *	Electrical Water Heater 200l (with feet)
0204-0105 *	Electrical Water Heater 300l (with feet)
0204-0107 *	Electrical Water Heater 300l Thrifase (with feet)
0204-0108 *	Electrical Water Heater 500l Thrifase (with feet)

\*Sob encomenda especial

Dimensões

Capacity (Lts)	80	100	150	150	200	200	300	300	500
Potency (W)	1500	2000	3000	3000	3000	3000	3000	6000	9 000
Electric power	230V AC	230V AC	230V AC	230V AC	230V AC	230V AC	230V AC	400V AC	400V AC
Heating time	2h50	2h35	2h35	2h35	2h20	2h20	2h20	1h30	2h35
Temperature control	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80
Installation Type	Parede	Parede	Parede	Solo	Parede	Solo	Solo	Solo	Solo
A - Height (mm)	075	1050	1300	1300	1650	1650	1700	1700	2000
B - Diameter (mm)	495	495	540	540	600	600	640	640	740
Cold water inlet	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	1" F
Hotwater exit	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	1" F
Sewage	1/2" F	1/2" F	1/2" F	1/2" F	1/2" F	1/2" F	1/2" F	1/2" F	1/2" F
DHW recirculation	-	-	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F
Temperature and pressure valve	-	-	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F	3/4" F

