INOX (A.Q.S.)





Boiler Electric

80 la 500 Litrii

Principais Caraterísticas

Cuva din oțel inoxidabil AISI 316L; Nu are nevoie de un anod de magneziu; Densitate mare de izolare din poliuretan.

Descrição do Produto

Incalzitoare de stocare a apei construite din otel inoxidabil AISI 316L, extrem de rezistent la coroziune de perforații, toate sudurile efectuate de TIG eliminându-se astfel orice posibilitate de coroziune interstițială. Disponibil cu capacități de la 80 la 500 de litri.

Modelos e Preços

Código	Modelo
0204-0201	Electrical Water Heater 80I (wall mounted)
0204-0202	Electrical Water Heater 100l (with feet)
0204-0203	Electrical Water Heater 150l (wall mounted)
0204-0103 *	Electrical Water Heater 150l (with feet)
0204-0204	Electrical Water Heater 200l (wall mounted)
0204-0104 *	Electrical Water Heater 200l (with feet)
0204-0105 *	Electrical Water Heater 300l (with feet)
0204-0107 *	Electrical Water Heater 300l Thrifase (with feet)
0204-0108 *	Electrical Water Heater 500l Thrifase (with feet)

^{*}Sob encomenda especial







Dimensões

Capacity (Lts)	80	100	150	150	200	200	300	300	500
Potency (W)	1500	2000	3000	3000	3000	3000	3000	6000	9 000
Electric power	230V AC	400V AC	400V AC						
Heating time	2h50	2h35	2h35	2h35	2h20	2h20	2h20	1h30	2h35
Temperature control	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80	0 - 80
Installation Type	Parede	Parede	Parede	Solo	Parede	Solo	Solo	Solo	Solo
A - Height (mm)	075	1050	1300	1300	1650	1650	1700	1700	2000
B - Diameter (mm)	495	495	540	540	600	600	640	640	740
Cold water inlet	3/4"F	3/4"F	3/4"F	3/4"F	3/4~F	3/4"F	3/4"F	3/4"F	1"F
Hot water exit	3/4"F	3/4"F	3/4"F	3/4"F	3/4~F	3/4"F	3/4"F	3/4"F	1"F
Sewage	1/2"F	1/2"F	1/2"F	1/2"F	1/2~F	1/2"F	1/2"F	1/2"F	1/2"F
DHW recirculation	-	-	3/4"F	3/4"F	3/4~F	3/4"F	3/4"F	3/4"F	3/4"F
Temperature and pressure valve	-	-	3/4"F						

