

VITRIFICADO (A.Q.S.)

Termosifon emailat (de la 150 la 300 litri)



Principais Caraterísticas

- Izolare termică rigidă din poliuretan de inalta densitate;
- Cuva din oțel;
- Invelis extern din otel inoxidabil AISI 316 sau otel vopsit;
- Include suport electric cu servicii și termosta de siguranța; Notă: Boilerele sunt echipate cu un anod de magneziu. Deoarece acestea sunt consumabile sunt excluse de la garanție.


Descrição do Produto

Incalzitor de apa produse pentru utilizare în sisteme solare de încălzire pe termosifon. Construită cu două straturi de vitrificare care protejează cuva de coroziune și asigurarea depozitării foarte igienic de apă caldă menajeră. Magneziul anod inclus oferă o protecție suplimentară împotriva coroziunii și electroliză. Pentru locații externe și instalare orizontală. Disponibil în capacități de 150, 200 și 300 de litri.

Modelos e Preços

Código	Modelo
0208-0701	Thermo-Siphon Water Heater 150l (Galvanized Casing)
0208-0301	Thermo-Siphon Water Heater 150l (Stainless Steel Casing)
0208-0702	Thermo-Siphon Water Heater 200l (Galvanized Casing)
0208-0704	Thermo-Siphon Water Heater 300l (Galvanized Casing)

Dimensões



TECHNICAL DATA	CAPACITY (LTS)	ELECTRICAL SUPPORT (W)	NOMINAL PRESSURE (BAR)	HEAT EXCHANGER (M²)	THERMAL INSULATION (MM)
Termosifon 150	150L	1500	6	0,60	43
Termosifon 200	200L	2000	6	0,68	43
Termosifon 300	300L	2000	6	0,85	43

