



Pressurized heat pipe kits

200L | 300L

Descrição do Produto

Pressurized CPC solar heat pipe kit for domestic hot water production with Solar Keymark certification. 316L stainless steel accumulator.

Kit composition:

- 15 (200L) or 20 (300L) Vacuum Pipes
- 1 316L stainless steel accumulator
- 1 support frame
- 1 automatic vent
- 1 T/P 1/2 safety valve"

Modelos e Preços

Código	Modelo
2799-0115K	Kit Solar Heat Pipe Pressurizado 200L (15 Tubos)
2799-0116K	300L Pressurized Solar Heat Pipe Kit (20 Pipes)
1702-0295	1500W 1" Electric Resistor (Optional)

TECHNICAL DICE	200	300
No. of Tubes	15	20
Total area (m²)	2,75	3,70
Accumulator capacity (Lts)	180	240
Accumulator steel	Inox SUS316L	Inox SUS316L
Thermal Insulation of the Accumulator	Polyurethane	Polyurethane
Distance between tubes (mm)	110	110
Tube length (mm)	1800	1800
Tube Outside Diameter (mm)	58	58
Max. operating temperature (°C)	99	99
Maximum working pressure (bar)	7	7
Stagnation Temperature (°C)	230	230
Length (mm)	1850	2430
Compression (mm)	1987	1987
Height (mm) - Terrace version	1200	1200
Support structure	Galvanized steel	Galvanized steel
Keymark Solar Certification	✓	✓

