



DEMETER NEO hydro stove

Central Heating

Principais Caraterísticas

- The Hydro Stove shall include:
- Touch controller with probes and high temperature wiring
 - Anti-condensatin valve
 - WILO circulator pump
 - Automatic draft regulator
 - Thermal insulation
 - 24L expansion vessel
 - Pressure safety valve 3 bar
 - Pressure gauge 4 bar
 - Trap
 - Thermal discharge safety valve 95 °C
 - Manual discharge/emptying valve
 - Piping in copper
 - 4 Floor levelers
 - Transport on site by pallet truck

Descrição do Produto

Wood hydro stove for central heating with screen-printed glass door and nominal thermal power of 20,8 kW. Energy class A+ and ECODESIGN 2022, which translates into equipment with high performance and low energy consumption. Hydraulic module included.
Installation Recommendations: chimney in AISI 316L stainless steel.

Modelos e Preços

Código	Modelo
0601-0230	Wood Hydro Stove DEMETER NEO (Central Heating)

TECHNICAL DATA	DEMETER NEO
Door	Serigraphed Glass
Cumbustible type	Wood
Nominal power (kW)	29
Average Water power (kW)	21,8
Average Air power(kW)	8,5
Yield (%)	75
Average combustion temperature(°C)	369
Wood consumption (kg/h)	4,8 a 9,0
Water volume (L)	68
Maximum pressure (bar)	3
Connection flow/return	1"
Sewer connection	3/4"
Chimney diameter (mm)	200
Maximum heated volume (m3)	853
Weight (kg)	300
Warranty	2 Anos

